

(12) UK Patent Application (19) GB (11) 2 275 331 (13) A

(43) Date of A Publication 24.08.1994

(21) Application No 9403441.0

(22) Date of Filing 23.02.1994

(30) Priority Data

(31) 245975

(32) 23.02.1993

(33) NZ

(71) Applicant(s)

John Stuart Fleming

20 Selwyn Street, Onehunga, Auckland, New Zealand

(72) Inventor(s)

John Stuart Fleming

(74) Agent and/or Address for Service

Frank B Dehn & Co

Imperial House, 15-19 Kingsway, LONDON,
WC2B 6UZ, United Kingdom

(51) INT CL⁵

F24C 3/04 15/22

(52) UK CL (Edition M)

F4W W1 W21 W46A W46B

F4S S35B

(56) Documents Cited

GB 2261942 A

GB 2216252 A

GB 2203532 A

GB 0681840 A

GB 0661919 A

GB 0571924 A

GB 0428393 A

(58) Field of Search

UK CL (Edition M) F4W

INT CL⁵ F24C

(54) Heating apparatus

(57) A heating apparatus comprises a burner 2, artificial fuel F and a reflector 11. The reflector 11 may be mounted so as to be retained in a curved shape. At least part of the combustion products may pass into the room to be heated via a catalytic converter 9. A door 18 may serve as a partial reflector. The burner front face 3 may be arranged in a bed of vermiculite 6.




FIG. 2.

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

GB 2 275 331 A




FIG. 1.




FIG.2.

A HEATING APPARATUS

This invention relates to heating apparatus
and more particularly to compact heating apparatus,
5 for example a fuel heating apparatus, such as a gas,
liquid or gel fuel enclosed or semi-enclosed heating
apparatus incorporating a visible flame and/or a
heating apparatus exhausting at least a portion of
the emissions from the combustion into the room in
10 which it is housed. This invention also relates to a
burner means for a heater.

Traditionally there has been a need for
heating apparatus to provide a combination of heat
and preferably the appearance of a traditional
15 fireplace, without the difficulties and
responsibilities which accompany traditional
fireplaces. These requirements have resulted in, in
some instances, fireplaces which are more
conveniently fuelled with fuels such as oils, gel or
20 gas, yet which provide artificial logs or coals to
create the impression of a fireplace. Whilst these
heating apparatus overcome the inherent limitations
of traditional fireplaces, yet retain an appearance
of the traditional fireplace, in many instances
25 there are severe limitations on their application in
view of the bulk of such fireplaces.

In the past, where space is at a premium, visual flame heating apparatus have usually been made as shallow as possible to allow them to a; fit into confined spaces and b; to minimise the quantity of material used and as such the cost of the apparatus.

One of the main factors limiting the extent to which a heating apparatus can be reduced in depth is the depth requirement required to approximate the depth of a traditional wood or coal fire with artificial logs or coals in a manner to make the apparatus visually acceptable. This problem is particularly evident in heating apparatus which employ, for example, two main artificial logs positioned substantially horizontally one behind the other on a grate or base as these units are usually of a similar depth to a traditional fire.

In the past, heating apparatus incorporating visual flame characteristics and an artificial log or coal "fire" of a narrower depth than traditional coal or wood fires have not been able to attract a significant share of the market.

There is also a need in the market place to provide heating apparatus which are able to be

mounted for operation close to a wall or other
portion of the building and in certain circumstances
to be rest within the wall cavity of a building, to
reduce the outward projection of the heating
5 apparatus into a room.

A particular difficulty of heater projection
arises in small rooms, hallways, hotel rooms and the
like however, it has been found that in view of the
10 close proximity of the heat source to particularly
the rear of a casing for a shallow heating
apparatus, there are increased problems of heat
transfer from a casing of the heater, thus limiting
the extent to which such heating apparatus can be
15 close mounted or recessed into a building wall,
particularly such wall incorporate flammable
material.

Another difficulty in the provision of heating
20 apparatus is the normal requirement to provide a
flue to an air space external of the room in which
the heater is mounted so as to exhaust the emissions
from the combustion. Residual gases and carbon
monoxide and other contaminate levels in these
25 emissions such as residual unburnt hydrocarbons
creating an unpleasant smell maybe too high to be
normally exhausted into the room in which the unit

is housed. The provision of the flue not only adds
difficulties in fitting a unit to an existing room
or building but also exhausts a large quantity of
heating out through the flue to the external
5 airspace.

It is an object of this invention to come some
way in overcoming mentioned problems or at least
provide the public with a useful choice.

10

Other aspects of this invention will become
apparent from the following description.

According to one aspect of this invention
15 there is a provided a burner means for a heater
including an actual or artificial fuel assembly,
outlet means for providing a flame about or adjacent
said fuel assembly, a reflective means positioned
behind said fuel assembly to reflect an image of at
20 least part of said fuel assembly and/or said flame
visible from a front of said burner means.

According to a further aspect of this
invention the reflective means is a sheet of
25 reflective material oriented in relation to
remaining portions of the apparatus to reflect an
image of at least portions of said fuel assembly

and/or flame to a front of said burner means to increase the apparent depth of the fuel assembly and/or flame to a viewer.

5 According to a still further aspect of this invention, the reflective means is mounted to a support such that upon thermoexpansive heating of said sheet, said sheet bends in at least one plane to reflect a visually reduced or enlarged image of
10 the portions of said fuel assembly or flame to a front of said burner means.

 According to a further aspect, the invention consists in a heating apparatus comprising
15 a primary combustion chamber;

 a flammable fluid supply to said primary combustion chamber;

 an air inlet into said primary combustion chamber;

20 a secondary combustion chamber in communication with said primary combustion chamber;

 a catalytic converter within or forming said secondary combustion chamber; and

 an exhaust port in communication with said
25 secondary combustion chamber such that the flammable fluid supplied to said heater is combusted first in the primary combustion chamber and at least a

portion of the products of the primary combustion further combusted in the catalytic converter before exiting through the exhaust port.

5 Other aspects of this invention which should be considered in all its novel aspects will become apparent from the following description.

10 One embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

15 Figure 1 is a substantially schematic view of the burner apparatus according to one embodiment of the invention in a substantially perspective view.

20 Figure 2 is a substantially schematic cross-sectional side view of an embodiment of heater apparatus incorporating the burner means of Figure 1 showing the heating apparatus positioned in a recess within a building wall.

25 With reference to Figures 1 and 2, the burner assembly as generally indicated by arrow 1 is preferably arranged for fuelling with gas, for example LPG or natural gas. Further, portions of the apparatus are preferably provided in substantially heat resistant material such as sheet

metal, for example stainless, surface treated mild steel and the like.

5 Whilst the illustrated embodiment is described with reference to gas fuelling or a flammable fluid, the invention is not limited thereto, and the invention is applicable across a wide range of fuel types.

10 The burner apparatus 1 preferably includes a burner housing 2 which is preferably formed in sheet steel and provides an inclined front face 3 which is, in a preferred form of the invention, arranged in a bed of vermiculite or other material which may in certain circumstances provide the appearance of
15 embers, particularly when percolated with gas.

The housing 2 preferably incorporates a fuel assembly F which is provided as an artificial log, for example formed in a ceramic material and the
20 like according to substantially known techniques.

In the preferred form, the fuel assembly is mounted substantially horizontally across a frontal portion of the housing 2 and adjacent a flame outlet
25 4 which is positioned at a level substantially below upper portions of the artificial log such that it is

substantially hidden from view in a normal line of sight.

5 With reference to Figure 2, it will be seen
that the housing 2 is fed with gas from a gas outlet
5 and also draws air to assist burning of said gas
from an inlet 6 in a heater housing generally
indicated by arrow 7 such that upon ignition, a
10 flame 8 preferably emanates as a sheet of flame in a
substantially natural manner from the outlet 4,
substantially adjacent the fuel assembly F. In a
preferred form of the invention, and with reference
to Figure 2, an exhaust pathway is provided via a
catalytic convertor 9 to an outlet 10 in the heater
15 casing 7.

 A reflective means 11 is provided behind the
burner outlet 4 and the fuel assembly F. In a
preferred form, the reflective means 11 is provided
20 as a sheet of polished stainless steel of a width
substantially commensurate with a back of the heater
casing 7. The reflectorised sheet 11 is oriented to
reflect, according to a range of normal lines-of-
sight, an image of said flames and portions said
25 fuel assembly F to thus create an increased apparent
depth and in this embodiment, an increase in the
apparent number of logs.

Preferably the reflective sheet 11 is spaced rearwardly from the burner housing 2 to provide an air pathway 12 therebetween and to maintain the reflective surface of the sheet 11 substantially spaced in use from the flame 8 by a curtain of air 13 which passes from a lower portion thereof upwardly across the reflective face of the sheet 11. Preferably a further air pathway 14 is preferably provided behind said reflective sheet 11 so as to enable a convection air flow between a rear wall 15 of a firebox 7a for the heating arrangement and the reflective sheet 11, so as to maintain a relatively controlled temperature of said reflective sheet 11 and to reduce heat transfer from the vicinity of said reflective sheet 11 rearwardly of the heater.

Preferably the reflective sheet 11 is securely mounted between upper and lower adjustable mounting blocks 16 to remaining portions of the heater and the dimensions of said reflective sheet 11 are such that surface of the reflective sheet 11 is retained in a curved, preferably outwardly concave shape so that the image reflected by reflective sheet 11 is dimensionally different, and preferably slightly smaller than the flames and fuel assembly F seen when viewed from the front of the heater. This

visually enforces the increased apparent depth of the fuel assembly and flames.

5 It is also envisaged that precurvature of the reflective sheet 11 reduces a likelihood that the reflective sheet 11 will develop ripples under the effects of thermo expansion as a result of heating from close proximity to the flames 8.

10 In a preferred form of the invention, the firebox rear wall 15 is preferably spaced from an outer casing 17 of the heater to additionally provide an air convection pathway therebetween.

15 The air convection pathway passes from the inlet 6 to the outlet 10 outside the firebox 7 and it will be appreciated that effectively three air convection pathways provided; (1) forwardly of said reflective sheet 11; (2) behind said reflective
20 sheet 11 and; (3) rearwardly of the firebox rear wall 15 provide an enhanced ability for transfer of heat in the region of those convection pathways out of the heater outlet 10 to reduce heat transmission to surrounding surfaces, for example wall
25 construction surfaces adjacent the heater casing 7.

In a preferred form of the invention, preferably the heater casing also incorporates an openable frontal door 18, although this is in no way essential to the invention. In one form of the invention, preferably the frontal door 18 is provided to be semi-reflectorised to provide multiple reflected images between the reflective sheet and the frontal door 18 for enhanced visual effect.

In view of the depth of the apparatus being substantially less than a substantially equivalent product not incorporating the reflective surface, the apparatus can be constructed at a reduced cost.

It should be noted that the apparatus as shown in Figure 2 comprise a flue or exhaust port 10 which directs emissions from the combustion directly into the room in which the heater is housed. The main fire box of the heater may be used as a primary combustion chamber and a secondary combustion chamber may be provided which includes, or in this case comprises, a catalytic converter 9. The provision of the catalytic converter to provide secondary combustion allows the emissions from the primary combustion chamber to be exhausted into the room without undesirable levels of carbon monoxide

of unburnt hydrocarbons. This is particularly difficult to achieve when trying to provide a visual flame as opposed to the cleaner burning blue or invisible flames.

5

The catalytic converter 9 used in the secondary combustion chamber should be chosen to provide a suitable flow through to exhaust either the entire products of combustion or a portion of those products should an alternative exhaust flue be provided. This flow through the catalytic converter 9 must be balanced against the input of flammable fluid and the oxygen levels to ensure a properly visible flame is provided.

10

15

A suitable catalytic converter has been found to be a CORNING 7x2 catalytic converter which provides a suitable flow at an input rate of fuel of 12 to 14 MJ/h. This has been found suitable for this particular embodiment although other converters and input rates could be used.

20

It should be noted that the option of passing only a portion of the exhaust through the catalytic converter may be used where it is desired to return at least a portion of the heated air back into the room to improve the heating achieved by the

25

apparatus and this may be done even when an external flue is provided to transport the remainder of the exhaust gases to an external air space. This external flue may take a flow of exhaust either
5 prior or subsequent to the catalytic converter.

For the catalytic converter to operate efficiently, a minimum temperature is necessary in the area surrounding the catalytic converter.
10 Generally, a minimum temperature of greater than 200°C is required for the efficient operation of the catalytic converter 9 and it has been found that a working temperature of about 240°C or greater is particularly suitable. To achieve this temperature,
15 the heater housing and exhaust port must be constructed so as to provide a large quantity of heat to the area surrounding the catalytic converter 9 and as can be shown in the embodiment in Figure 2, the provision of the catalytic converter 9 directly
20 adjacent at the top of the primary combustion chamber will allow sufficient heat from the primary combustion chamber to be used to provide the correct operating temperature for the catalytic converter 9.

25 It has also been found that in order to get a large anaesthetically acceptable flame height, the oxygen percentage in the flue gases should be in the

range of 2% to 10%. This is particularly important on smaller sized units which use less input of flammable fluid.

5 Thus it will be appreciated that one embodiment of the apparatus provides for a burner or heater apparatus which facilitates the exhausting of emissions directly into the room in which the heater is housed to improve the heat produced by that
10 heater into the room as well as perhaps making the provision of an external flue unnecessary and thereby reducing costs in fitting such apparatus.

15 Thus it will be appreciated that at least preferred embodiments of the apparatus provide for a burner/heating apparatus which facilitates a visual flame having the apparent depth of a much deeper arrangement, and which incorporates convection pathways which reduce heat transfer rearwardly of the heater casing to facilitate
20 mounting of the apparatus in a convenient and compact manner.

25

CLAIMS:

1. A burner means for a heater including an
actual or artificial fuel assembly, outlet
5 means for providing a flame about or adjacent
said fuel assembly, a reflective means
positioned behind said fuel assembly to
reflect an image of at least part of said fuel
assembly and/or said flame visible from a
10 front of said burner means.
2. A burner means as claimed in Claim 1 wherein
the reflective means is a sheet of reflective
material oriented in relation to remaining
15 portions of the apparatus to reflect an image
of at least portions of said fuel assembly
and/or flame to a front of said burner means
to increase the apparent depth of the fuel
assembly and/or flame to a viewer.
20
3. A burner means as claimed in Claim 1 or Claim
2 wherein the reflective means is mounted to a
support such that upon thermoexpansive heating
of said sheet, said sheet bends in at least
25 one plane to reflect a visually reduced or
enlarged image of the portions of said fuel

assembly or flame to a front of said burner means.

4. A heater apparatus comprising:
- 5 a primary combustion chamber;
a flammable fluid supply to said primary combustion chamber;
an air inlet into said primary combustion chamber;
- 10 a secondary combustion chamber in communication with said primary combustion chamber;
a catalytic converter within or forming said secondary combustion chamber; and
- 15 an exhaust port in communication with said secondary combustion chamber such that the flammable fluid supplied to said heater is combusted first in the primary combustion chamber and at least a portion of the products
- 20 of the primary combustion further combusted in the catalytic converter before exiting through the exhaust port.
5. A heater apparatus as claimed in claim 4 wherein said flammable fluid comprises a
- 25 flammable gas such as natural gas or liquidified petroleum gas.

6. A heater apparatus as claimed in claim 4 or claim 5 wherein said apparatus operates with a substantial portion of yellow flame provided in the primary combustion chamber.

5 7. A heater apparatus as claimed in claim 4 wherein said apparatus includes control means to ignite and/or regulate and/or control the fuel supplied to said primary combustion chamber.

10 8. A heater apparatus as claimed in claim 4 wherein said exhaust port at least partially exhausts directly from the apparatus into a room in which the apparatus may be housed.

15 9. A heater apparatus substantially as hereinbefore described with reference to the accompanying drawings.

10. A burner means substantially as hereinbefore described with reference to the accompanying drawings.

20

25

Patents Act 1977 Searcher's report to the Comptroller under Section 17 (The Search report)	Application number GB 9403441.0
Relevant Technical Fields (i) Int Cl (Ed.M) F4W (ii) Int Cl (Ed.5) F24C	Search Examiner A N BENNETT
Databases (see below) (i) UK Patent Office collections of GB, EP, WO and US patent specifications.	Date of completion of Search 24 MARCH 1994
(ii)	Documents considered relevant following a search in respect of Claims :- 1-3

Categories of documents

X: Document indicating lack of novelty or of inventive step.	P: Document published on or after the declared priority date but before the filing date of the present application.
Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.	E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.
A: Document indicating technological background and/or state of the art.	&: Member of the same patent family; corresponding document.

Category	Identity of document and relevant passages		Relevant to claim(s)
X:Y:P	GB 2261942 A	(HEPWORTH) whole document	X: 1-2 Y: 3
X:Y	GB 2216252 A	(VALOR) whole document	X: 1-2 Y: 3
X:Y	GB 2203532 A	(GLOW-WORM) whole document	X: 1-2 Y: 3
Y	GB 0681840	(WRIGHT). see reflector B	3
Y	GB 0661919	(BAINES). whole document	1
Y	GB 0571924	(PREMIER). see reflector 11	3
Y	GB 0428393	(GUILUX). whole document	3

Databases:The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).